

SPECIFICATION

anyS!gn!
anyFlex!



บริษัท จีเทคโอเอชเอ็ม จำกัด
G-TECH OHM CO.,LTD.
ศูนย์ค้าส่งวัสดุสิ่งพิมพ์นานาชนิด

AMX5 NO LINER/ CODE : SF-AMX5-X.XX-50M (no liner)

APPLICATION

Building murals
Building Wraps and Scaffolding cover
X-stand Advertising
Display (indoor-outdoor)
Booth Exhibition
Curtain
Advertisement allows wind flow and light weight

SPECIFICATION

Weight	270 g/m ²
Base material	Polyester
Surface	Matt
Width	2.50, 2.80, 3.20 m.
Length	50 m.
Core	3"
Yard x Threat	1,000x1,000 D (12x12)

COMPATIBILITY

Ink Compatibility

ECO

Solvent

UV-
Curable

Printer Compatibility

Most Solvent & Eco Solvent, UV Curable Printing system: LATEX & HP, Agfa-Jeti, Epson, Roland, Mimaki, Mutoh, Seiko, Océ, VUTEK, Scorpion, Keundo, etc.

TEST RESULTS

	UNIT	RESULTS	TEST METHOD
Tensile Strength	lbs/in	235/178	FS#191 5102
Elongation	%	28.3	FS#191 5102
Tear Strength	lbs	48/34	FS#191 5134

GUIDELINES

Printing Tip : Dry time will vary depending on ink type.

Storage : It is recommended to store in the closed original packing in a cool and dry environment

Shelf Life : One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may effect results.