

# SPECIFICATION

*anyS!gn!*  
*anyFlex!*



บริษัท จีเทคโอเอชเอ็ม จำกัด  
G-TECH OHM CO.,LTD.  
ศูนย์ค้าส่งวัสดุสิ่งพิมพ์นานาชนิด

## AMX5 WITH PVC LINER / CODE : SF-AMX5-PVC-X.XX-50M (with liner)

### APPLICATION

Building murals  
Building Wraps and Scaffolding cover  
X-stand Advertising  
Display (indoor-outdoor)  
Booth Exhibition  
Curtain  
Advertisement allows wind flow and light weight

### SPECIFICATION

|               |                       |
|---------------|-----------------------|
| Weight        | 270 g/m <sup>2</sup>  |
| Base material | Polyester             |
| Surface       | Matt                  |
| Width         | 2.50, 2.80, 3.20 m.   |
| Length        | 50 m.                 |
| Core          | 3"                    |
| Yard x Threat | 1,000x1,000 D (12x12) |

### COMPATIBILITY

#### Ink Compatibility

ECO

Solvent

UV-  
Curable

#### Printer Compatibility

Most Solvent & Eco Solvent, UV Curable Printing system: LATEX & HP, Agfa-Jeti, Epson, Roland, Mimaki, Mutoh, Seiko, Océ, VUTEK, Scorpion, Keundo, etc.

### TEST RESULTS

|                  | UNIT   | RESULTS | TEST METHOD |
|------------------|--------|---------|-------------|
| Tensile Strength | lbs/in | 235/178 | FS#191 5102 |
| Elongation       | %      | 28.3    | FS#191 5102 |
| Tear Strength    | lbs    | 48/34   | FS#191 5134 |

### GUIDELINES

**Printing Tip :** Dry time will vary depending on ink type.

**Storage :** It is recommended to store in the closed original packing in a cool and dry environment

**Shelf Life :** One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.  
All material should be tested by purchaser to determine final suitability. Printer and ink change may effect results.