

SPECIFICATION

anyS!gn!
anyFlex!



บริษัท จีเทคโอเอชเอ็ม จำกัด
G-TECH OHM CO.,LTD.
ศูนย์ค้าส่งวัสดุสิ่งพิมพ์นานาชนิด

ANY FLEX II / CODE : SF-AF-II-X.XX-50M

APPLICATION

Light box graphic
Backlit Trade show display
Department store display, Transit Displays
Luminous advertising
Metro illuminated signage
P.O.P. Display
Self-adhesive vinyl, Screen printing and digital printing

SPECIFICATION

Caliper	0.56 mm.
weight	610 g/m ²
Base material	Polyester
Surface	Semi-Gloss
Width	2.54 m./ 2.84/ 3.24 m.
Lenght	50 m.
Special Treatment	Anti-wickink. Anti-mildew.

COMPATIBILITY

Ink Compatibility

ECO



Solvent



UV-
Curable



Printer Compatibility

Most Solvent & Eco Solvent, UV Curable Printing system : LATEX &
HP, Agfa-Jeti, Epson, Roland, Mimaki, Mutoh, Seiko, Oce, VUTEk, Scorpion, Keundo, etc.

TEST RESULTS

		RESULTS	TEST METHOD
Cut Strip Tensile (lbs / in)	Wrap	160	FS#191 5102
	Weft	180	FS#191 5102
Elongation (%)	Wrap	26	FS#191 5102
	Weft	24	FS#191 5102
Tongue Tear (lbs)	Wrap	33	FS#191 5136
	Weft	30	FS#191 5136
Adhesion (lbs / in)	Wrap	20.0	FS#191 5970
	Weft	12.0	FS#191 5970

Yarn x Threat 500x1,000 (18x12)

GUIDELINES

Printing Tip : Dry time will vary depending on ink type.

Storage : It is recommended to store in the closed original packing in a cool and dry environment

Shelf Life : One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.

All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.