



GS3200

Superwide Format Solutions

Achieve Superwide Productivity AND Photorealistic Quality without Compromise

EFI's VUTEk® GS3200 flatbed and roll-to-roll UV printer revolutionizes superwide format printing by delivering the powerful combination of superior photorealistic quality and high productivity you need to grow your business and differentiate yourself from the competition.

Without compromising quality or productivity, the VUTEk GS3200 from EFI™ will extend your printing capabilities by offering a wider range of applications – from exhibition graphics, fine art, photographic reproduction and point-of-purchase displays to signage, banners, posters and commercial graphics. EFI's VUTEk GS3200 prints to a large range of direct to substrate materials and replaces multiple lower productivity printers so you can be more profitable and productive than ever before.

VUTEk DNA makes your business more productive, profitable and successful by offering:

Photorealistic Quality

- True 1000 dpi for high-precision print quality.
- Twelve-picoliter droplet technology for all colors, including white.
- Advanced three-layering capabilities for High Definition Point-of-Purchase graphics.
- Crisp four-point text.

Superwide Productivity

- Sellable, quality output at up to 2400 ft²/hr (223 m²).
- Continuous board-to-board, board-to-sheet and roll-to-roll printing capabilities.
- High production capacity in less floor space, allowing same-day Order-to-Delivery.

Uncompromised Versatility

- Eight-color, white and Fast-5™ capabilities in one printer for photorealistic quality at production speeds.
- Dual resolution of 600 dpi (24pL) or 1000 dpi (12 pL) for superior graphics that set you ahead of your competition.
- Ready for roll-to-roll and rigid substrate capabilities.
- Dual-roll capability that enables printing up to two 60-inch (152.4 cm) rolls simultaneously.



efi® print to win.



GS3200

VUTEK GS3200

Features and Benefits

- Eight-color plus white switchable to Fast-5™.
- Up to 2400 ft²/hour (223 m²/hour) and 44 - 4'x8' (1.2m x 2.4m) sheets per hour.
- Dual resolution: 600 dpi (24pL) or 1000 dpi (12 pL) selectable.
- High Definition Print (HDP).
- White printing capability allows printing white in six variations (overprint, underprint, spot, underspot, fill and overspot).
- Changeover to print on flexible from rigid substrates in less than one minute.
- Print directly to substrate - eliminates mounting and lamination of flexible materials for rigid application.
- Designed to complement continuous shifts and 24-hour production capability.
- 24 x 7 technical support.

Media/Handling

- Handles flexible or rigid substrates up to 126.5" (321.3 cm) wide and up to 2" (5.08 cm) thick.
- 2-up roll capability.
- Optional Heavy Duty Unwinder available for heavy roll-to-roll shops.
- Optional Extension Table with casters for use attached to printer or as a workstation.
- Optional Small Depth Extension Table for use with small boards/panels and multiple fence stops.

Productivity

- Fast-5™ - 2400 ft² (223 m²) per hour.
 - Production up to 44 (4' x 8') (1.2m x 2.4m) boards per hour.
- Eight-color plus white - 1200 ft² (111.4 m²) per hour.
 - Production up to 22 (4' x 8') (1.2m x 2.4m) boards per hour.

Environmental Considerations

- Compressed Air: 95 - 150 maximum at 4 cf/m (0.11 cm/m) — dry air only (not included).
- Temperature: 68° F to 85° F (20° C to 30° C).
- Humidity: 30% to 80% (non-condensing).
- Machine Weight: 6385 lbs. (2902 kg).
- Height: 64.75" (164.5 cm).
- Width: 249" (632.5 cm).
- Depth: 65" (165.1 cm), 157.7" (400.6 cm) with tables.
 - o + 5" (12.7 cm) unwinder.
 - o + 5" (12.7 cm) rewinder.
- Electrical: 3 phase, 60 amps (4 wire Delta or 5 wire Y), 200-240 VAC, 50/60 Hz.

Fiery XF RIP

- Optimized for use with the EFI Fiery® XF RIP.
- Advanced, easy-to-use, wizard-guided color tools for consistent, predictable, high-quality color.
- Powerful production tools include nesting, step and repeat, scaling, cropping and tiling.
- Advanced ICC color management for reliable color, quality output and proofing-quality color.
- Scalable, versatile platform grows with your needs when your business grows.

Inks

- VUTEK inks are supplied in 5.0-liter containers.
- Available in cyan, magenta, yellow, black, light cyan, light magenta, light yellow, light black and white.

Enhanced Service Plans (ESP)

- EFI's industry-leading service and support program.
- Predictable up-time to maximize profitability.
- Thirteen months of Essential level coverage, providing you with 24-business hour (three-business day) response.
- Eligible for upgrade to:
 - Critical – Providing eight-business hour (one-business day) response.
 - ProActive – Providing 16-business hour (two-business day) response.



One VUTEK Place
Meredith, NH 03253
603-279-4635
www.efi.com/VUTEK

Auto-Count, Bliss, Changing the Way the World Prints, ColorWise, Command WorkStation, DocBuilder, DocBuilder Pro, DocStream, EDOX, EFI, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, OneFlow, PrinterSite, PrintFlow, PrintMe, PrintSmith Site, Prograph, Proteus, RIP-While-Print, Setting the Standard in Digital Printing, Ultravu and VUTEK are registered trademarks of Electronics for Imaging, Inc. in the U.S. Patent and Trademark Office and/or certain other foreign jurisdictions. Bestcolor is a registered trademark of Electronics for Imaging GmbH in the U.S. Patent and Trademark Office. AutoCal, Balance, BioVu, BioWare, Build, ColorCal, Digital StoreFront, Estimate, Fiery Link, Fiery Prints, Fiery Spark, FreeForm, Hagen, JetTrion, Logic, MicroPress, PhotoXposure, PrintCafe, PrintSmith, PSI, PSI Flexo, RemoteProof, RIPChips, Scan, Screenproof, SendMe, Splash, Spot-On, UltraTex, UV Series 50, VisualCal, WebTools, the EFI logo, the Fiery Prints logo and Essential to Print are trademarks of Electronics for Imaging, Inc. Best, the Best logo, Colorproof, PhotoXposure, RemoteProof, and Screenproof are trademarks of Electronics for Imaging GmbH. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.
© 2009 Electronics for Imaging



Superwide Format Solutions