

SPECIFICATION



GEKKO JET / CODE : GJ-W-30CP-X.XX-50M

Gekko Jet is monomeric calendered glossy white PVC glossy vinyl film with self adhesive. applying solvent ink. single PE paper release liner

APPLICATION

Advertisement Media
Label, Packaging
Cutout Standing Media
Display, Exhibition Decoration
Wall Decoration
Indoor / Outdoor media (1 year)

SPECIFICATION

thickness	0.11 mm.
softness	28 PHR
Base material	Monomeric PVC
Surface	White Gloss
Width	0.914, 1.07, 1.27, 1.37, 1.52 m.
Lenght	50 m.
Liner	120 gsm single side PE treated premium paper, one side siliconized 15g/inch
Liner Strange	15g/inch
Compatibilities	suitable for all the solvent based ink large format printer

COMPATIBILITY

Ink Compatibility



Excellent to be applied in digital outdoor eco-solvent and solvent based inkjet printing machines for signage display, vehicle graphics, subway, and glass wall.

Printer Compatibility

Most Solvent & Eco Solvent, UV Curable Printing system: LATEX & HP, Agfa-Jeti, Epson, Roland, Mimaki, Mutoh, Seiko, Oce, VUTEK, Scorpion, Keundo, etc.

TECHNICAL DATA

Solvent acrylic pressure sensitive gelatin, permanent
- glue thickness : 20 mic.
- stick on SUS 20 min. peel off strength : 1400g/25mm
- stick on glass 20min. peel off strength : 700g/25mm
- stick on lacquer 20 min. peel off strength : 650g/25mm

GUIDELINES

Printing Tip :	Dry time will vary depending on ink type.
Storage :	It is recommended to store in the closed original packing in a cool and dry environment
Shelf Life :	One year stored in original package in recommended condition
Recommend :	storage between temperature 15-25 degree Celsius and 35-65% relative humidity.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All Material should be tested by purchaser to determine final durability. Printer and ink change may also affect result.